



SPECIFICATIONS

Supports Over 40 lbs Per SQ. FT.

Injection-Molded Polyethylene

Reinforced with Uniform Ribbing

Inset Bottom Reduces Shifting

Designed for Full Bottom Support

Pad Size Molded into Sides

OVERVIEW

PolarPad™ by DuraPlas is a durable, lightweight polyethylene base for HVAC and other light, ground-supported equipment. Injection molded with uniform underside ribbing for strength, it features a textured top and rounded edges that deliver a clean, concrete-like appearance. Ideal for air conditioning condensers, heat pumps, and pool filters, the PolarPad should be fully supported and installed on compacted soil, gravel, or a hard surface for optimal performance.

FEATURES

- **Lightweight Design** allows for easy, one-person installation with no additional equipment required.
- **Textured, Slip-Resistant Surface** with a self-leveling design.
- **UV, Weather, and Chemical Resistant**, including oils, refrigerants, and canine urine.
- **Engineered for Strength and Durability** with resistance to impact, cracking, and warping.

POLARPAD™

Dial No.	Dimensions			Weight lbs	Max. Load* lbs	Color
	Width	Length	Height			
84210	18"	38"	3"	8.9	1250	Black
84310	18"	38"	3"	8.9	1250	Gray
84220	24"	24"	2"	6	1210	Black
84320	24"	24"	2"	6	1210	Gray
84221	24"	24"	3"	7.4	1260	Black
84321	24"	24"	3"	7.4	1260	Gray
84222	24"	36"	3"	11	1300	Black
84322	24"	36"	3"	11	1300	Gray
84223	24"	48"	3"	13.6	1400	Black
84323	24"	48"	3"	13.6	1400	Gray
84230	30"	30"	2"	8.6	1250	Black
84330	30"	30"	2"	8.6	1250	Gray
84231	30"	30"	3"	12.4	1300	Black
84331	30"	30"	3"	12.4	1300	Gray
84232	30"	40"	3"	16.2	1700	Black
84332	30"	40"	3"	16.2	1700	Gray
84233	32"	32"	2"	9.7	1480	Black
84333	32"	32"	2"	9.7	1480	Gray
84234	32"	32"	3"	13	1440	Black
84334	32"	32"	3"	13	1440	Gray

Dial No.	Dimensions			Weight lbs	Max. Load* lbs	Color
	Width	Length	Height			
84235	36"	36"	2"	12.3	1540	Black
84335	36"	36"	2"	12.3	1540	Gray
84236	36"	36"	3"	16.1	1500	Black
84336	36"	36"	3"	16.1	1500	Gray
84237	36"	48"	3"	21.2	1850	Black
84337	36"	48"	3"	21.2	1850	Gray
84238	36"	54"	3"	26	1720	Black
84338	36"	54"	3"	26	1720	Gray
84239	38"	42"	3"	18.2	1700	Black
84339	38"	42"	3"	18.2	1700	Gray
84240	40"	40"	3"	18	1710	Black
84340	40"	40"	3"	18	1710	Gray
84241	45"	58"	3"	36.5	2050	Black
84341	45"	58"	3"	36.5	2050	Gray
84242	48"	48"	3"	32	1900	Black
84342	48"	48"	3"	32	1900	Gray
84250	52"	52"	3"	37.5	2100	Black
84350	52"	52"	3"	37.5	2100	Gray

*LOAD SHOULD BE DISTRIBUTED EVENLY ACROSS PAD SURFACE TO GIVE MAXIMUM ALLOWABLE LOAD RATING.