



OVERVIEW

Dial® Side Open Metallic AC Disconnects are designed for fast, reliable installation in applications where space above the box is limited. Reversible door hinges minimize fitment issues, while the wide-swing door (greater than 180°) provides easy access to internal connections. Fusible models include LED indicators that clearly illuminate when a fuse is missing or blown. The NEMA 3R rain and sleet resistant powder-coated steel enclosure protects against rust and corrosion.

SPECIFICATIONS

120/240V / Single Phase

30A and 60A Ratings

NEMA 3R Metallic Enclosure

Copper and Aluminum Wire Compatible

cULus Listed

FEATURES

- Reversible Door Hinges reduce installation fitment problems.
- Wide Swing Door (greater than 180°) provides easy access to connections, simplifying installation and service in tight spaces.
- LED Indicators illuminate when a fuse is missing or blown for at-a-glance fuse status (fusible models only).
- Plated Copper Hardware resists corrosion and ensures optimal conductivity and smooth operation.
- Powder-Coated Galvanized Steel enclosure resists corrosion and rust.

SIDE OPEN AC DISCONNECTS

Dial No.	Description	Dimensions			Quantity
		Height	Width	Depth	
76115	60A Non-Fusible Disconnect	7.5"	5"	2.6"	10
76125	30A Fusible Disconnect	8.6"	5.2"	2.9"	10
76135	60A Fusible Disconnect	8.6"	5.2"	2.9"	10