



## OVERVIEW

Dial® 60A Non-Fusible Surge-Guard Disconnect features an easy-to-use pullout with integrated surge protection, making installation as simple as a traditional disconnect. The pullout can be easily disconnected and reinstalled during routine service calls. Housed in a NEMA 3R rain and sleet resistant enclosure, LED indicators are visible through the front window, providing clear, at-a-glance confirmation of surge protection device (SPD) status without opening the enclosure.

## SPECIFICATIONS

- 60A Non-Fusible
- 240V / Single Phase
- NEMA 3R Metallic Enclosure
- 25kA SCCR Rating
- 10kA Nominal Discharge Current
- UL / UL1449 Listed

## FEATURES

- Integrated Type-2 SPD contained within the pullout.
- Fully Protected Internal SPD housed safely inside the disconnect.
- Standard Installation—installs like a traditional AC disconnect.
- No Additional Wiring Required for SPD functionality.
- Red/green LED Indicators provide clear, at-a-glance SPD status.
- Anti-UV Powder-Coated Steel side-open enclosure.

## 60A NON-FUSIBLE SURGE-GUARD

Dial No.	Description	Dimensions			Quantity
		Height	Width	Depth	
76140	60A Non-Fusible Disconnect with Type-2 Surge Protection in the Pullout	8.4"	5"	3"	6
76141	Replacement 60A Non-Fusible Surge Protection Pullout	—	—	—	—