



**OVERVIEW**

Dial® Top Open Metallic AC Disconnects are designed for fast, reliable installation in applications where space on either side of the box is limited. The cover and internal composite shield can be removed without tools, enabling quick, hassle-free access for inspection and service. Plated copper hardware ensures smooth operation, optimal conductivity, and long-term corrosion resistance. The NEMA 3R rain and sleet resistant powder-coated steel enclosure protects against rust and corrosion.

**SPECIFICATIONS**

- 120/240V / Single Phase
- 30A and 60A Ratings
- NEMA 3R Metallic Enclosure
- Copper and Aluminum Wire Compatible
- cULus Listed

**FEATURES**

- **Easy Access Design**—cover and internal composite shield can be removed without tools.
- **Plated Copper Hardware** resists corrosion and ensures optimal conductivity and smooth operation.
- **Powder-Coated Galvanized Steel** enclosure resists corrosion and rust.
- **6 Multi-Size Knockouts** on 4 sides provide flexible installation options.

**TOP OPEN AC DISCONNECTS**

Dial No.	Description	Dimensions			Quantity
		Height	Width	Depth	
76110	60A Non-Fusible Disconnect	7.5"	5.2"	2.4"	10
76120	30A Fusible Disconnect	8.8"	5.2"	2.4"	10
76130	60A Fusible Disconnect	8.8"	5.2"	2.4"	10